

VS15

OPEN FRAME, ALL-IN-ONE

Quick Info

Display: 15" TFT, 1024x768
Processor: Intel® Core™ i7/i5/Celeron
Memory: 2x DDR3 (up to 8GB)
Chipset: Intel® QM57 Express
Graphics: Intel® HD Graphics
USB Ports: 6x USB 2.0/1.1

This all-in-one unit is designed to support a wide range of DFI-ACP motherboards, including those with Intel® Celeron, Core™ i5 and i7 processors. Our compact VS Series, interactive, touchscreen computer is designed for high-volume applications and is extremely cost effective. Its low-profile form-factor can be easily integrated into almost any custom enclosure.



VS15 SPECIFICATIONS

Construction:	Galvanized Steel
LCD Panel:	15" TFT, 1024x768, 250 nits, 500:1 contrast, 16.7M colors (8 bits per channel)
Touchscreen:	Elo AccuTouch 5-Wire Resistive/ Elo IntelliTouch Surface Wave/ 3M™ MicroTouch™ ClearTek™ II Capacitive/ or none
Main Board:	DFI CP100-NRM
Processor:	Intel® Core™ i7/i5/Celeron
Chipset:	Intel® QM57 Express
Memory:	2x DDR3, SO-DIMM up to 8GB (800/1066MHz)
Expansion Slots:	1x PCI
Storage:	Up to 2x Notebook HDDs with optional shockmount kit
Optical Drive:	Optional, 1x slim CD/DVD R/RW (not available if 2 HDDs are present)
Graphics:	Intel® HD Graphics
Graphics Ports:	1x VGA, 1x DVI-I (DVI-D signal only)
Audio:	Realtek ALC262, 2-channel High Definition Audio
Audio Ports:	1x Line-in, 1x Line-out, 1x Microphone
PS/2 Ports:	1x Keyboard, 1x Mouse
RJ45 LAN Ports:	2x Gigabit LAN
USB Ports:	6x USB 2.0/1.1
DB-9 Serial Ports:	2
Power Supply:	AC: ATX, 200W, 110-220V with power factor correction and noise-killer feature DC: Optional 12/20/24V
Ventilation:	2x 60mm chassis fans
Operating Temperature:	0 to 45°C, 10-90% RH
Storage Temperature:	-20 to 70°C, 5-95% RH
Dimensions (WxDxH):	373.6mm x 91.6mm x 289.9mm (14.71" x3.61" x 11.41")
Weight:	14.20 lbs
Mounting Options:	Open-frame
Optional Items:	Front Bezel: NEMA 4 (black, powder-coated) or NEMA 4X (brushed-stainless steel)